




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : B60R 25/10	A1	(11) International Publication Number: WO 92/10387 (43) International Publication Date: 25 June 1992 (25.06.92)
<p>(21) International Application Number: PCT/GB91/02193</p> <p>(22) International Filing Date: 10 December 1991 (10.12.91)</p> <p>(30) Priority data: 9026853.3 11 December 1990 (11.12.90) GB 9104798.5 7 March 1991 (07.03.91) GB</p> <p>(71) Applicant (for all designated States except US): FORECOURT SECURITY SYSTEMS LIMITED [GB/GB]; 14 Meteor Close, Airport Industrial Estate, Norwich NR6 6HG (GB).</p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): SCOTT, Peter [GB/GB]; 9 Blofield Road, Brundall, Norwich NR13 5NN (GB).</p>	<p>(74) Agent: LOVEN, Keith, James; Loven & Co., Dixon Street Business Centre, 108-116 Dixon Street, Lincoln LN6 7DA (GB).</p> <p>(81) Designated States: AT, AT (European patent), AU, BB, BE (European patent), BF (OAPI patent), BG, BJ (OAPI patent), BR, CA, CF (OAPI patent), CG (OAPI patent), CH, CH (European patent), CI (OAPI patent), CM (OAPI patent), CS, DE, DE (European patent), DK, DK (European patent), ES, ES (European patent), FI, FR (European patent), GA (OAPI patent), GB, GB (European patent), GN (OAPI patent), GR (European patent), HU, IT (European patent), JP, KP, KR, LK, LU, LU (European patent), MC (European patent), MG, ML (OAPI patent), MN, MR (OAPI patent), MW, NL, NL (European patent), NO, PL, RO, SD, SE, SE (European patent), SN (OAPI patent), SU⁺, TD (OAPI patent), TG (OAPI patent), US.</p> <p>Published With international search report. With amended claims.</p>	

(54) Title: VEHICLE PROTECTION SYSTEM



(57) Abstract

A vehicle protection system comprises a sensor (4), a transmission means (6), a control unit (8) and an alarm (10) signalling means. The sensor (4) is mountable on and capable of detecting interference with a vehicle (2), and the transmission means (6) is also mountable on the vehicle (2) and is activated in response to detection by the sensor (4) of interference with the vehicle to transmit a signal to the control unit (8). The control unit (8) is located remotely from the vehicle (2) and is arranged to activate the alarm (10) signalling means in response to receipt of said signal, there being no physical connection between the control unit (8) and the transmission means (6).

+ DESIGNATIONS OF "SU"

Any designation of "SU" has effect in the Russian Federation. It is not yet known whether any such designation has effect in other States of the former Soviet Union.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MG	Madagascar
AU	Australia	FI	Finland	ML	Mali
BB	Barbados	FR	France	MN	Mongolia
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GN	Guinea	NL	Netherlands
BJ	Benin	GR	Greece	NO	Norway
BR	Brazil	HU	Hungary	PL	Poland
CA	Canada	IT	Italy	RO	Romania
CF	Central African Republic	JP	Japan	SD	Sudan
CG	Congo	KP	Democratic People's Republic of Korea	SE	Sweden
CH	Switzerland	KR	Republic of Korea	SN	Senegal
CI	Côte d'Ivoire	LI	Liechtenstein	SU ⁺	Soviet Union
CM	Cameroon	LK	Sri Lanka	TD	Chad
CS	Czechoslovakia	LU	Luxembourg	TC	Togo
DE	Germany	MC	Monaco	US	United States of America
DK	Denmark				

VEHICLE PROTECTION SYSTEM

Field of the Invention

The invention relates to vehicle protection systems.

Background to the Invention

In many instances where vehicles are left in areas to which the public have relatively easy access, there exist the dual problems of firstly theft of or from the vehicles, and secondly damage to the vehicles. It is now common to use a so-called "car alarm" in certain vehicles which may be sensitive to an intrusion (using, for instance, an ultrasonic detector) but these have several limitations: (1) due to the high number of false alarms they are often ignored; (2) they are difficult to install and remove quickly from a variety of vehicles; (3) they do not allow for centralised control of a number of such alarms; and (4) they are of little use in areas that are relatively sparsely populated.

There is, therefore, a clear need for an improved vehicle protection system.

Summary of the Invention

According to the present invention, there is provided a vehicle protection system comprising a sensor, a transmission means, a control unit and an alarm; the sensor is mounted on the vehicle and is capable of detecting an interference with the vehicle; the transmission means, also mounted on the vehicle, is activated by the sensor detecting

- 2 -

an interference with the vehicle and causes the transmission means to transmit a signal to the control unit; the control unit is located remotely from the vehicle; on receiving the signal from the transmission means the control unit activates the alarm.

According to the present invention there is also provided a site protection system comprising a sensor, a transmission means, a control unit and an alarm; the sensor is mounted in, or at the periphery of the site and is capable of detecting an interference with the site (e.g. a vibration, pressure, the breaking of a beam of radiation, etc); the transmission means, also mounted in or at the periphery of the site, is activated by the sensor detecting an interference on or at the periphery of the site and causes the transmission means to transmit a signal to the control unit; the control unit is located remotely from the sensor; on receiving the signal from the transmission means the control unit activates the alarm.

Normally the sensor in the immediately preceding paragraph will be located at the periphery of the site (e.g. on a fence or gate).

The invention will now be described, by way of example only, with reference to the drawings that follow; in which:

Brief Description of the Drawings

- 3 -

Figure 1 is a schematic representation of the present invention in use;

Figure 2 is a block diagram representing the configuration and operation of the present invention;

Figure 3 is a flow diagram also representing the operation of the present invention;

Figure 4 is a schematic representation of a further embodiment of the present invention; and

Figure 5 is a schematic representation of yet another embodiment of the invention.

Description of the Preferred Embodiments

Referring now to Figure 1, there is shown a vehicle 2 on which is mounted a sensor 4, which is itself connected to a transmission means 6 also mounted on the vehicle 2. In this case the sensor 4 and the transmission means 6 are mounted within the vehicle 2. Although the vehicle 2 shown is clearly a car, the invention is applicable to other vehicles such as motor cycles, boats, caravans, plants etc.

Also shown schematically in Figure 1 is a control unit 8 and an alarm 10. The alarm 10 may be any device or means intended to attract attention to the vehicle 2, examples of suitable alarms 10 will be given below.

- 4 -

Figure 2 shows the preferred construction of the system in block diagram form. Figure 3 explains the operation of the system in flow diagram format which may be understood with reference to the key set out below.

KEY

- 100- START
- 101- Has the ultrasonic scanner 12 detected an interference?
- 102- Has the piezo-crystal sensor 14 detected an interference?
- 103- Is the control unit 8 armed?
- 104- Activate first-stage alarm.
- 105- Activate siren 16.
- 106- Activate stroboscopic light source 18.
- 107- Activate vocal alarm through speakers 22.
- 108- Has another interference been detected within the first pre-set time period?
- 109- Activate second-stage alarm.
- 110- Activate auto-dialler 20.
- 111- Activate 2kW lighting source 24.

The sensor 4 includes a detector of movement within the vehicle 2, such as an ultrasonic scanner 12, and a shock and motion detector, such as a piezo-crystal sensor 14 which can be set to be capable of detecting scratches due to the vibrations they cause in the vehicle bodywork and is also

- 5 -

capable of detecting other interferences with the vehicle 2 of a mechanical nature. Thus, in combination, the ultrasonic scanner 12 and the piezo-crystal sensor 14 (which together constitute the sensor 4) are between them capable of detecting interference with the outside of the vehicle 2 such as scratching or denting, etc; and interference with the inside of the vehicle 2 such as the movement of a person therein or the motion of glass fragments from a broken window, etc.

The sensitivity of the ultrasonic scanner 12 and/or the piezo-crystal sensor 14 can be adjusted to achieve a balance between the level of security achieved with the system and the occurrence of false alarms in the particular circumstances involved.

If the sensor 4 detects an interference with the vehicle 2 it causes the transmission means 6 to transmit a signal S1. The transmission means 6 is in wireless communication with the control unit 8. The transmission means 6 comprises a low power VHF radio frequency transmitter on an approved frequency (currently 418 MHz), the emitted signal S1 is coded to avoid interference with neighbouring signals S and to deter illegitimate attempts to interfere with the system. The coding may be factory-set or programmable.

- 6 -

In their operating construction the sensor 4 and the transmission means 6 are combined in a single self-contained unit; they have been described separately here for simplicity.

The ultrasonic scanner 12 and the piezo-crystal sensor 14 are included within the unit which is powered by an integral nickel-cadmium battery-pack (not shown) to enable the unit to be properly portable; the battery-pack is capable of powering the unit for between 2 and 10 days, a battery power level indicator may be included in the system. A storage rack (not shown) may be included as part of the system in to which one, or more, combined sensor/transmission units 4,6 may be deposited; the storage rack includes a trickle-type battery recharger to re-energise the battery-pack. The sensor/transmission units 4,6 include female sockets which mate with powered pins on the rack. The unit may include a light-emitting diode powered by the battery-pack to act as a further visual deterrent.

The coded signal S1 from the transmission means is received by the control unit 8 which is located remotely from the vehicle. The receiver is also of an approved type. The control unit 8 may be wall-mounted, either on the outside of a premises in a well-known burglar alarm housing, or inside a premises; the unit may also be desk-mounted or mounted in any other convenient fashion. Portable recharge-

- 7 -

able models may be provided for domestic use. In advanced models the coded signals S are specific to certain sensors 4 enabling the actual source of the signal S1 to be uniquely identified. In some models different signals may be used to indicate whether it is the ultrasonic scanner 12 or the piezo-crystal sensor 14 that has detected the interference. In such a system the control unit 8 may be linked to a printer which generates details of the source, the time and the date of the signal S1. All of the constructions are tamper-proof.

The control unit 8 also includes switching means for arming and disarming the system. The switching means may be toggled between the armed and disarmed states using a remote-control system utilising a 418 MHz signal used with a different coding, although other well known remote control systems may be used, for instance the infra-red remote-control systems that are well known in the field of car-alarms. When the vehicle protection system is armed this is indicated by the activation of a light emitting diode.

The unit 8 is powered in its normal usage by a standard linkage to a mains (240 volts, a.c.) power supply. However, the unit may be battery powered for use in circumstances where a mains power supply is not available and, in any event, may include a 24 hour back-up battery

- 8 -

power supply which operates in the event of a primary power failure. The battery power source (not shown) is charged from the mains power supply when connected thereto.

On receiving the coded signal S1 from the transmission means 6, the control unit 8 activates the alarm 10. The alarm 10 is a multi-stage warning and alert system comprising a first-stage alarm that occurs for a first pre-set time period, nominally 10 seconds, and a second-stage alarm that occurs for a second pre-set time period, nominally 20 minutes, if a coded signal S1 is received again within the first pre-set time period of the first-stage alarm. The unit 8 will also activate the second-stage alarm if another coded signal S is received from one of its associated sensors 4 even if that signal S is not identical to the first coded signal S1 received.

The multi-stage response allows for a first-stage that acts to warn off intruders who may be innocent prospective customers or members of the public, whilst the second-stage provides a high level of security for the vehicles.

The first-stage alarm comprises: (i) an audio warning that is emitted throughout the first pre-set time period from a siren 16; and (ii) the activation of a stroboscopic light source 18, both of which may be obtained as proprietary items. The light source 18 is a 100 Watt source that

- 9 -

is not intended for general exterior illumination, but merely to act as a warning and to attract attention to the area.

The second-stage alarm comprises the continued emission of sound from the siren 16 and the continued activation of the stroboscopic light source 18 for the further second pre-set time period, and (at the start of the second pre-set time period) the activation of an auto-dialler 20 to alert at least one interested party, such as the owner of the vehicle 2 or the police, to the interference. Auto-diallers 20 are well known proprietary items that will automatically dial a pre-set number (or numbers) and deliver a pre-programmed, or pre-recorded message - the auto-dialler 18 used in the preferred embodiment of the present invention described herein dials up to four different telephone numbers in sequence.

The first and second-stage alarms are combined in the control unit 8 in the preferred construction, although they have been described as separate elements for simplicity.

The first and second-stage alarms may be improved by the addition of the following add-on features described below. The basic system includes provision for the subsequent addition of these features enabling the vehicle pro-

- 10 -

tection system to be targeted at a wide range of applications. The add-on features are shown using dashed lines in Figures 2 and 3.

The first-stage alarm improvement comprises a vocal audio warning instead of the siren audio warning (or alternatively the vocal audio warning may alternate with the siren audio warning). The vocal audio warning involves the use of a pre-recorded, or pre-programmed, message that can be relayed through a 30 Watt audio amplifier and thence through two weather-proof speakers 22 to deliver a polite warning to the intruder of the presence of the vehicle protection system and the consequences should their actions be continued.

The second-stage alarm improvement comprises the attachment to the unit 8 of a 2kW lighting source 24 that is capable of illuminating the vehicle 2 during the second-stage alarm time period. The lighting source 24 may be turned on and off at a rate of about 80 times per minute to alert passers-by to the illuminated area and, in particular, to the intruders; it therefore acts as a powerful deterrent.

The system may be assembled in its various embodiments from materials and components that are readily available, and the actual construction of the system will be apparent from the above description to one skilled in the art.

- 11 -

It is to be noted that sensors 4 may be installed in a plurality of vehicles and all monitored by the control unit 8 (or interfaced control units). Furthermore, the first and second pre-set time periods may be re-set if required.

Such an arrangement has the additional advantage that the sensors 4 may be grouped in to zones, a video camera may have a number of monitoring positions - preferably at least one per zone. Thus if a sensor 4 detects an interference in a zone the camera may be directed towards that zone. This arrangement reduces the need for a plurality of cameras and quickens the response time of the camera compared to a panning camera. Once again this increases the deterrent level of the system.

The vehicle protection system described above provides a high level of security whilst cutting down the number of false alarms. When the system is used to protect vehicles displayed on a point of sale forecourt the likelihood of a genuine prospective customer setting off a full scale alarm is minimised and thus the likelihood of a prospective customer being alienated by setting of an alarm is reduced.

Further examples embodying the present invention will now be described, by way of example only.

Further Embodiment 1

- 12 -

In order to provide security for guests' cars at a hotel the present invention may be provided for their use on a rental basis, a charge normally being added to the guest's bill.

In this embodiment each of the sensors 4 may selectively activated from the control unit 8, and a substantially unique signal is emitted by the respective transmission means 6 associated with each sensor 4 if an interference is affected. Thus, control may be maintained over the hired systems, for instance by ensuring that they require regular coded reactivation from the control unit 8, to minimise thefts of the systems and difficulties with over-hiring or confusions between guests. Furthermore, a signal S1 may be uniquely correlated to a known guest for readily apparent reasons of convenience and efficiency.

The control unit 8 may comprise a computer based control system that stores vehicle details (including e.g car make, car model, car colour, car registration, car location, owner and owner's whereabouts).

Other applications for this embodiment, with or without the presence of the charging element, include airports, railway stations, ports, hospitals, educational establishments, government facilities etc.

Further Embodiment 2

- 13 -

This embodiment is illustrated in Figure 4 in which like numerals have been used to identify like parts. A combined sensor 4 and transmitter 6 - for this embodiment identified as transceiver 26 - is attached to one end of a length of security material 28, such as wire rope, chain or metal bar(s). The transceiver 26 may be formed or placed around the security material 28, or attached thereto (as shown) by a linkage 30 at least as strong as the material 28. The other end 32 of the material 28 includes a linkage member 34 that can be releasably attached to the transceiver 26, for instance by a padlock type linkage or an internal locking latch. The preferred construction includes a locking means within the transceiver 26 that engages the linkage member 34 and which can be opened by a key, combination and/or coded signal.

The length of security material 28, with the transceiver 26 attached, may then be threaded through, for instance, the spokes of a motor bike or the fittings of a boat's outboard motor.

The sensor 4 within the transceiver 26 may detect, for instance, a disturbance (as above), the material 28 being cut, the ends of the material 28 being withdrawn from the transceiver 26 or a movement of the article being pro-

- 14 -

tected. On detecting such an interference the transmitter 6 is activated and the alarm sequence commences as set out above.

This embodiment may also be used to protect other vehicles, e.g. caravans or boat trailers by attaching the material 28 to, or around, the tow hitch of the caravan or trailer. The transceiver 26 may alternatively be attached directly to the tow hitch.

This embodiment may also be used in the surveillance of perimeter gates, haulage containers, bicycles, secure areas and/or construction equipment.

Further Embodiment 3

Figure 5 illustrates a system in accordance with the invention which can be used to monitor large numbers of vehicles, for example in a car-park covering a very large area, or in several spaced car-parks. Each vehicle 50, of which only three are illustrated in each zone for clarity, is provided with a combined sensor/transmitter unit 51. The sensor includes as a detector element any one or more of a wide range of movement or heat detectors, for example a Hall Effect detector, in which movement of a magnetic element adjacent to a Hall Effect transistor produces a detectable electrical charge, a piezo-electric detector or a passive infra-red detector.

- 15 -

Detection of interference with a vehicle, for example giving rise to vibration, or the presence of detectable body heat from an intruder, sends a signal to a microprocessor controlling the operation of the sensor/transmitter unit. The signal causes a first code and a second code to be retrieved from a store within the unit and to be sent to the transmitter, which broadcasts an FM signal at, for example, 418 Mhz, comprising the two codes. The first code is a permanently stored system-identifying code which prevents adjacent systems interfering with each other, and the second is a user-entered unit-identifying code. This latter code is entered into the device via a keypad on the unit, with a display, for example a liquid crystal display, to show the numbers registered. The codes may be scrambled before transmission in accordance with a system key and unscrambled on receipt, as a further security measure.

In the example illustrated in Figure 5, unit 124 in Zone 1 has been caused to send a signal, and this is received by Zone 1 control unit 52, suitably mounted at an elevated point within the zone, for example on a pole 53. The control unit 52 in turn retrieves from its store an identifying code which is added to the unit code, and this is then transmitted via a 27 Mhz FM transmitter in the control unit to a central control panel 54 which could, for example, be situated at a distance of about 2 miles from

- 16 -

Zone 1. The central control panel has displays 55 and 56 (for example liquid crystal displays), which show the Zone number and unit number identified in the received signal after unscrambling.

By this embodiment of the system an individual vehicle being interfered with can be immediately identified at a remote control centre, and security staff despatched to investigate, for example.

Each sensor/transmitter unit may be powered by a rechargeable battery, for example a nickel-cadmium battery, so that the unit is readily transportable from one vehicle to another. As an alternative, for example for vehicle fleet use, the unit can be permanently attached to the vehicle and supplied with power from the vehicle's electrical system. The zone control units 52 may also be battery powered, or may be permanently located and supplied with mains electric power.

The central control panel may also cause the sending of alarms and the initiation of other warning signals in response to receipt of a signal. For example, the panel may incorporate an auto-dialler as hereinbefore described.

CLAIMS

1. A vehicle protection system, comprising a sensor, a transmission means, a control unit and an alarm signalling means, wherein the sensor is mountable on and capable of detecting interference with a vehicle, the transmission means is also mountable on the vehicle and is activated in response to detection by the sensor of interference with the vehicle to transmit a signal to the control unit, the control unit is located remotely from the vehicle and is arranged to activate the alarm signalling means in response to receipt of said signal, there being no physical connection between the control unit and the transmission means.

2. A system according to Claim 1, wherein the transmission means comprises a store for storing an identifying code and means for including said code in the transmitted signal, and the control unit comprises means for detecting the code in the received signal and for activating the alarm signalling means in response to detection of the code.

3. A system according to Claim 2, wherein the control means comprises a store for storing a plurality of different codes, and means for comparing the detected code with

- 18 -

the stored codes and for activating the alarm signalling means only when the detected code matches one of the stored codes.

4. A system according to Claim 2 or 3, wherein the transmission means and the control unit each comprise means for entering an identifying code into the respective store.

5. A system according to Claim 4, wherein each code entering means comprises a keypad.

6. A system according to Claim 5, wherein the code entering means also comprises a display means.

7. A system according to any of Claims 2 to 6, wherein the transmission means comprises means for scrambling the code before its inclusion in the transmitted signal, and the detection means in the control unit comprises means for unscrambling the received signal to produce the code.

8. A system according to any of Claims 2 to 7, wherein the alarm signalling means is arranged to activate an audible alarm.

9. A system according to any of Claims 2 to 8, wherein the alarm signalling means is arranged to activate a visible warning device.

10. A system according to any of Claims 2 to 9, wherein the alarm signalling means is arranged to activate a telephone dialling and messaging device.

- 19 -

11. A system according to any preceding claim, comprising a plurality of said control units, each arranged to receive signals from any of a plurality of sensors within a respective zone, and each capable of communicating with a control alarm signalling means in a manner not requiring a physical connection between the control unit and the central alarm signalling means.

12. A system according to Claim 11, wherein each control unit is adapted to transmit an identifying signal to the central alarm signalling means comprising a first code identifying the control unit and a second code identifying the sensor signalling.

AMENDED CLAIMS

[received by the International Bureau on 12 May 1992 (12.05.92);
original claim 1 amended; new claims 13 and 14 added;
other claims unchanged (2 pages)]

1. A vehicle protection system, comprising: a self-contained sensor unit containing a sensor and a transmission means; a control unit; and an alarm signalling means; wherein the sensor unit is mountable on and capable of detecting interference with a vehicle, the transmission means being activated in response to detection by the sensor of interference with the vehicle to transmit a signal to the control unit, and the control unit is located remotely from the vehicle and is arranged to activate the alarm signalling means in response to receipt of said signal, there being no physical connection between the control unit and the transmission means.

2. A system according to Claim 1, wherein the transmission means comprises a store for storing an identifying code and means for including said code in the transmitted signal, and the control unit comprises means for detecting the code in the received signal and for activating the alarm signalling means in response to detection of the code.

3. A system according to Claim 2, wherein the control means comprises a store for storing a plurality of different codes, and means for comparing the detected code with _____

11. A system according to any preceding claim, comprising a plurality of said control units, each arranged to receive signals from any of a plurality of sensor units within a respective zone, and each capable of communicating
5 with a control alarm signalling means in a manner not requiring a physical connection between the control unit and the central alarm signalling means.

12. A system according to Claim 11, wherein each control unit is adapted to transmit an identifying signal
10 to the central alarm signalling means comprising a first code identifying the control unit and a second code identifying the sensor signalling.

13. A system according to any preceding claim, wherein the sensor unit comprises more than one sensor.

15 14. A system according to Claim 13, wherein the sensor unit includes an ultrasonic scanner and a piezo-crystal sensor.

1/3




Fig. 1




Fig. 2

2/3




Fig. 3

3/3




Fig. 4




Fig. 5

INTERNATIONAL SEARCH REPORT

International Application No PCT/GB 91/02193

I. CLASSIFICATION OF SUBJECT MATTER (If several classification symbols apply, indicate all) *		
According to International Patent Classification (IPC) or to both National Classification and IPC IPC ⁵ : B 60 R 25/10		
II. FIELDS SEARCHED		
Minimum Documentation Searched ¹		
Classification System	Classification Symbols	
IPC ⁵	B 60 R	
Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in the Fields Searched ²		
III. DOCUMENTS CONSIDERED TO BE RELEVANT³		
Category ⁴	Citation of Document, ⁵ with indication, where appropriate, of the relevant passages ⁶	Relevant to Claim No. ⁷
X	EP, A2/3, 0 366 378 (HARADA) 02 May 1990 (02.05.90), see totality.	1, 2, 3, 10
X	US, A, 4 821 309 (NAMEKAWA) 11 April 1989 (11.04.89), see totality.	1, 2, 3, 10
X	GB, A, 2 198 270 (WILSON) 08 June 1988 (08.06.88), see totality.	1, 2, 3, 9
X	GB, A, 2 220 778 (AUTOMATED SECURITY) 17 January 1990 (17.01.90), see totality.	1, 2, 3
X	DE, A1, 3 908 029 (BLAUPUNKT) 13 November 1990	1, 2, 3
<div style="display: flex; justify-content: space-between;"> <div style="width: 48%;"> <p>⁸ Special categories of cited documents: ⁹</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="width: 48%;"> <p>¹⁰ later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>¹¹ document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>"I" document member of the same patent family</p> </div> </div>		
IV. CERTIFICATION		
Date of the Actual Completion of the International Search	Date of Mailing of this International Search Report	
25 February 1992	12 MAR 1992	
International Searching Authority	Signature of Authorized Officer	
EUROPEAN PATENT OFFICE	<div style="display: flex; align-items: center;"> Mme N. KUIPER </div>	

Form PCT/ISA/210 (second sheet) (January 1985)

III. DOCUMENTS CONSIDERED TO BE RELEVANT (CONTINUED FROM THE SECOND SHEET)		
Category *	Citation of Document, " with indication, where appropriate, of the relevant passages	Relevant to Claim No.
X	<p>(13.11.90), see totality. --</p> <p>DE, C1, 3 918 052 (BLAUPUNKT) 22 November 1990 (22.11.90), see totality. ----</p>	1,2,3

ANHANG
zum internationalen Recherchen-
bericht über die internationale
Patentanmeldung Nr.

ANNEX
to the International Search
Report to the International Patent
Application No.

ANNEXE
au rapport de recherche inter-
national relatif à la demande de brevet
international n°

PCT/GB91/02193 SAE 54106

In diesem Anhang sind die Mitglieder
der Patentfamilien der im obenge-
nannten internationalen Recherchenbericht
angeführten Patentedokumente angegeben.
Diese Angaben dienen nur zur Unter-
richtung und erfolgen ohne Gewähr.

This Annex lists the patent family
members relating to the patent documents
cited in the above-mentioned inter-
national search report. The Office is
in no way liable for these particulars
which are given merely for the purpose
of information.

La présente annexe indique les
membres de la famille de brevets
relatifs aux documents de brevets cités
dans le rapport de recherche inter-
national visée ci-dessus. Les renseigne-
ments fournis sont donnés à titre indica-
tif et n'engagent pas la responsabilité
de l'Office.

Im Recherchenbericht angeführtes Patentedokument Patent document cited in search report Document de brevet cité dans le rapport de recherche	Datum der Veröffentlichung Publication date Date de publication	Mitglied(er) der Patentfamilie Patent family member(s) Membre(s) de la famille de brevets	Datum der Veröffentlichung Publication date Date de publication
EP-A2- 366378	02-05-90	EP-A3- 366378 JP-A2- 2116231	10-10-90 27-04-90
US-A - 4821309	11-04-89	JP-A2-62011364	20-01-87
GB-A - 2198270		GB-A0- 8629249 GB-A1- 2198270	14-01-87 08-06-88
GB-A - 2220778		DK-A0- 6487/88 DK-A - 6487/88 EP-A2- 350554 EP-A3- 350554 GB-A0- 8816449 GB-A1- 2220778 NO-A0- 885176 NO-A - 885176 US-A - 4910493	21-11-88 12-01-90 17-01-90 28-11-90 17-08-88 17-01-90 21-11-88 12-01-90 20-03-90
DE-A1- 3908029	13-09-90	DE-C2- 3908029 EP-A2- 387581 EP-A3- 387581 DE-C1- 3918052	13-12-90 19-09-90 11-09-91 22-11-90
DE-C1- 3918052	22-11-90	EP-A2- 387581 EP-A3- 387581 DE-A1- 3908029 DE-C2- 3908029	19-09-90 11-09-91 13-09-90 13-12-90

THIS PAGE BLANK (USPTO)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)

THIS PAGE BLANK (USPTO)